

Innenzahnkränze

geradeverzahnt

aus Messing Ms 58
Eingriffswinkel 20°


Roues à denture intérieure

à denture droite

en laiton Ms 58
angle de pression 20°

	Type No.	Zähne dents	d	di	d-h8	b
Modul 0,5	Mg 540 Zi	40	20.0	19.0	36	4
	Mg 545 Zi	45	22.5	21.5	40	4
	Mg 548 Zi	48	24.0	23.0	40	4
	Mg 550 Zi	50	25.0	24.0	45	4
	Mg 555 Zi	55	27.5	26.5	45	4
	Mg 560 Zi	60	30.0	29.0	50	4
	Mg 565 Zi	65	32.5	31.5	55	4
	Mg 570 Zi	70	35.0	34.0	55	4
	Mg 580 Zi	80	40.0	39.0	60	4
	Mg 590 Zi	90	45.0	44.0	70	4
Mg 5100 Zi	100	50.0	49.0	70	4	
Modul 0,7	Mg 740 Zi	40	28.0	26.6	48	6
	Mg 745 Zi	45	31.5	30.1	50	6
	Mg 748 Zi	48	33.6	32.2	55	6
	Mg 750 Zi	50	35.0	33.6	55	6
	Mg 755 Zi	55	38.5	37.1	60	6
	Mg 760 Zi	60	42.0	40.6	65	6
	Mg 765 Zi	65	45.5	44.1	70	6
	Mg 770 Zi	70	49.0	47.6	70	6
	Mg 780 Zi	80	56.0	54.6	80	6
	Mg 790 Zi	90	63.0	61.6	85	6
Mg 7100 Zi	100	70.0	68.6	95	6	
Modul 1,0	Mg 1030 Zi	30	30.0	28.0	55	8
	Mg 1036 Zi	36	36.0	34.0	60	8
	Mg 1040 Zi	40	40.0	38.0	65	8
	Mg 1045 Zi	45	45.0	43.0	70	8
	Mg 1048 Zi	48	48.0	46.0	75	8
	Mg 1050 Zi	50	50.0	48.0	75	8
	Mg 1055 Zi	55	55.0	53.0	80	8
	Mg 1060 Zi	60	60.0	58.0	85	8
	Mg 1065 Zi	65	65.0	63.0	90	8
	Mg 1070 Zi	70	70.0	68.0	95	8
Mg 1080 Zi	80	80.0	78.0	105	8	
Mg 1090 Zi	90	90.0	88.0	115	8	
Mg 10100 Zi	100	100.0	98.0	125	8	

Modul 0,5



Modul 0,7

Modul 1,0

Fett gedruckt ab Lager lieferbar / Caractères gras disponible du stock

Innenzahnkränze

Roues à denture intérieure


geradeverzahnt

Vergütungsstahl C 45
Eingriffswinkel 20°

à denture droite

acier à améliorer C 45
angle de pression 20°

Modul 1,0



Type No.	Zähne dents	d	di	d-h8	b
Sg 1025 Zi	25	25.0	23.0	50	8
Sg 1030 Zi	30	30.0	28.0	55	8
Sg 1032 Zi	32	32.0	30.0	60	8
Sg 1036 Zi	36	36.0	34.0	60	8
Sg 1040 Zi	40	40.0	38.0	65	8
Sg 1045 Zi	45	45.0	43.0	70	8
Sg 1048 Zi	48	48.0	46.0	75	8
Sg 1050 Zi	50	50.0	48.0	75	8
Sg 1055 Zi	55	55.0	53.0	80	8
Sg 1060 Zi	60	60.0	58.0	85	8
Sg 1065 Zi	65	65.0	63.0	90	8
Sg 1070 Zi	70	70.0	68.0	95	8
Sg 1072 Zi	72	72.0	70.0	100	8
Sg 1080 Zi	80	80.0	78.0	105	8
Sg 1090 Zi	90	90.0	88.0	115	8
Sg 10100 Zi	100	100.0	98.0	125	8
Sg 10120 Zi	120	120.0	118.0	150	8
Sg 1525 Zi	25	37.5	34.5	70	12
Sg 1530 Zi	30	45.0	42.0	75	12
Sg 1532 Zi	32	48.0	45.0	80	12
Sg 1536 Zi	36	54.0	51.0	85	12
Sg 1540 Zi	40	60.0	57.0	90	12
Sg 1545 Zi	45	67.5	64.5	100	12
Sg 1548 Zi	48	72.0	69.0	100	12
Sg 1550 Zi	50	75.0	72.0	105	12
Sg 1555 Zi	55	82.5	79.5	112	12
Sg 1560 Zi	60	90.0	87.0	120	12
Sg 1565 Zi	65	97.5	94.5	120	12
Sg 1570 Zi	70	105.0	102.0	135	12
Sg 1572 Zi	72	108.0	105.0	140	12
Sg 1580 Zi	80	120.0	117.0	150	12
Sg 1590 Zi	90	135.0	132.0	170	12
Sg 15100 Zi	100	150.0	147.0	190	12
Sg 15120 Zi	120	180.0	177.0	220	12
Sg 2030 Zi	30	60.0	56.0	95	16
Sg 2036 Zi	36	72.0	68.0	107	16
Sg 2040 Zi	40	80.0	76.0	115	16
Sg 2045 Zi	45	90.0	86.0	125	16
Sg 2048 Zi	48	96.0	92.0	131	16
Sg 2050 Zi	50	100.0	96.0	135	16
Sg 2055 Zi	55	110.0	106.0	145	16
Sg 2060 Zi	60	120.0	116.0	155	16
Sg 2065 Zi	65	130.0	126.0	165	16
Sg 2070 Zi	70	140.0	136.0	175	16
Sg 2072 Zi	72	144.0	140.0	185	16
Sg 2080 Zi	80	160.0	156.0	195	16
Sg 2090 Zi	90	180.0	176.0	220	16
Sg 20100 Zi	100	200.0	196.0	240	16

Modul 1,5

Modul 2,0

Fett gedruckt ab Lager lieferbar / Caractères gras disponible du stock